



DEPARTMENT OF PERMITTING, ENVIRONMENT, AND REGULATORY AFFAIRS (PERA)
BOARD AND CODE ADMINISTRATION DIVISION

MIAMI-DADE COUNTY
PRODUCT CONTROL SECTION
11805 SW 26 Street, Room 208
Miami, Florida 33175-2474
T (786) 315-2590 F (786) 315-2599
www.miamidade.gov/pera

NOTICE OF ACCEPTANCE (NOA)

American Industrial Manufacturers of Building Materials
6505 West Park Blvd. suite 306-360
Plano, TX. 75093

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed and accepted by Miami-Dade County PERA - Product Control Section to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Section (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. PERA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Section that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the Florida Building Code including the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: AIM Coatings, Adhesives & Cements

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of pages 1 through 5.

The submitted documentation was reviewed by Alex Tigera.



NOA No.: 12-0203.11
Expiration Date: 04/17/13
Approval Date: 05/24/12
Page 1 of 5

ROOFING COMPONENT APPROVAL

Category: Roofing
Sub-Category: Cements, Coatings and Adhesives
Materials Asphalt
Fire Classification: See General Limitation #1

EVIDENCE SUBMITTED

<u>Test Agency</u>	<u>Test Identifier</u>	<u>Test Name/Report</u>	<u>Date</u>
PRI Asphalt Technologies, Inc.	051301	ASTM D 2824-85 Type III	06/08/94
PRI Asphalt Technologies, Inc.	034401	ASTM D 2824-85 Type I	06/08/94
PRI Asphalt Technologies, Inc.	041401	ASTM D 4479-93 Type I	06/08/94
PRI Asphalt Technologies, Inc	013401	ASTM D 41	06/08/94
PRI Asphalt Technologies, Inc	239301	ASTM D 3019-85 Type III	06/08/94
PRI Asphalt Technologies, Inc	088401	ASTM D 2824-85 Type III	06/08/94
PRI Asphalt Technologies, Inc	293301	ASTM D 3019-85 Type III	06/08/94
PRI Asphalt Technologies, Inc	039402	ASTM D 2824-85 Type III	06/08/94
PRI Asphalt Technologies, Inc	089301	ASTM D 4479-93 Type I	06/20/94
PRI Asphalt Technologies, Inc	172407	ASTM D 4586-93 Type I	06/21/94
PRI Asphalt Technologies, Inc	172407	ASTM D 3409-81	06/21/94
PRI Asphalt Technologies, Inc	144409	ASTM D 4586-93 Type I	06/20/94
PRI Asphalt Technologies, Inc	144409	ASTM D 3409-81	06/21/94
PRI Asphalt Technologies, Inc	086404	ASTM D 3019-85 Type III	06/08/94
PRI Asphalt Technologies, Inc	125411	ASTM D 4479-93 Type I	06/08/94
PRI Asphalt Technologies, Inc	162423	ASTM D 4586-93 Type I	06/20/94
PRI Asphalt Technologies, Inc.	PRI00003	ASTM D 3019 Type III	04/10/00
PRI Asphalt Technologies, Inc.	PRI00004	ASTM D 5643	04/13/00
PRI Asphalt Technologies, Inc	BRW-116-02-01	ASTM D 3409	07/30/04
Underwriters Laboratories Inc.	TGJR.R15837	Physical Properties Certification	08/26/04
Momentum Technologies, Inc	DX16A8A	ASTM D 1227	01/23/08



NOA No.: 12-0203.11
Expiration Date: 04/17/13
Approval Date: 05/24/12
Page 2 of 5

PHYSICAL PROPERTIES OF COMPONENTS

Trade name:	# 560 Premium Fibrated Aluminum Roof Coating
Specifications:	ASTM D 2824 Type III
Description:	A premium blend of refined bitumen, solvents, high quality leafing aluminum pigments and with non-asbestos reinforcing fibers for additional strength and durability. Its high aluminum pigment concentration provides a highly reflective tough coating over B.U.R. systems, modified bituminous membranes and metal surfaces. Brush or spray applied at a rate of 1 to 2 gallons per 100 ft ² .
Container Size:	5, 55 gallons. Note all cautions on container label.
Systems Approvals:	Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance.
Trade name:	#540 Premium Non-Fibrated Aluminum Roof Coating
Specifications:	ASTM D 2824 Type I
Description:	A superior blend of bitumen, solvents, and brilliant aluminum pigments for long term durability. Forms a highly reflective coating over B.U.R. systems, modified bituminous membranes and metal surfaces. Brush, roller, or spray applied at a rate of ½ to 1 gallon per 100 ft ² .
Container Size:	5, 55 gallons. Note all cautions on container label.
Systems Approvals:	Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance
Trade name:	#510 Standard Non-Fibrated Aluminum Roof Coating
Specifications:	ASTM D 2824 Type I
Description:	A superior blend of bitumen, solvents, and brilliant aluminum pigments for long term durability. Forms a highly reflective coating over B.U.R. systems, modified bituminous membranes and metal surfaces. Brush, roller, or spray applied at a rate of ½ to 1 gallon per 100 ft ² .
Container Size:	5, 55 gallons. Note all cautions on container label.
Systems Approvals:	Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance
Trade name:	# 250 Fibered Roof Coating
Specifications:	ASTM D 4479 Type I
Description:	A special blend of selected oxidized bitumen, petroleum distillates and quality non-asbestos fillers and reinforcing fibers. It preserves and protects B.U.R. systems and metal roofs, prolonging service life. Brush, roller, squeegee or spray applied at a rate of 1 to 3 gallons per 100 ft ² on metal and composition roofs, and 5 to 8 gallons per 100 ft ² over embedded gravel roofs.
Container Size:	5, 55 gallons. Note all cautions on container label.
Systems Approvals:	Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance

Trade name: # 100 Asphalt Primer
Specifications: ASTM D 41
Description: A precise blend of oxidized asphalt and refined solvents, which penetrates porous surfaces. Enhances adhesion of built up roof, modified bituminous membrane systems, protective and reflective coatings. Brush, roller, or spray applied at a rate of ½ to 1 gallon per 100 ft².
Container Size: 5, 55 gallons. Note all cautions on container label.
Systems Approvals: Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance

Trade name: # 520 Standard Fibrated Aluminum Roof Coating
Specifications: ASTM D 2824 Type III
Description: Fortress Fibered Aluminum Roof Coating is a blend of bitumen, solvents, quality aluminum pigments and non-asbestos reinforcing fibers for additional strength and durability. Provides protective properties to a variety of roofing systems. Brush or spray applied at a rate of 1 to 2 gallons per 100 ft².
Container Size: 5, 55 gallons. Note all cautions on container label.
Systems Approvals: Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance

Trade name: # 600 Mod Bit Adhesive Brush Grade
Specifications: ASTM D 3019 Type III
Description: A polymer enriched single ply membrane adhesive. A blend of refined asphalt, solvents, tactifying resins, and SBS polymers blended together in precise proportions, to duplicate the properties of modified bituminous membranes. Trowel applied at a rate of 1 to 2 gallons per 100 ft².
Container Size: 1, 5, 55 gallons. Note all cautions on container label.
Systems Approvals: Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance

Trade name: # 300 Plastic Cement, #320 Wet/Dry Plastic Cement
Specifications: ASTM D 4586 Type I, and ASTM D 3409
Description: This blend of refined asphalts and adhesion promoters is designed to bond rapidly to moist, damp, wet or dry surfaces. It provides water repellence, and is used on asphalt shingle roofs, asphalt composition roofs, concrete or masonry surfaces and sealing areas where dissimilar materials join: chimneys, gutters, valleys, etc. Trowel or putty knife apply at a rate of 12 ft², 1/8" thick per gallon.
Container Size: 5 gallons. Note all cautions on container label.
Systems Approvals: Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance



Trade name:	#340 Flashing Cement
Specifications:	ASTM D 4586 Type I, and ASTM D 3409
Description:	This blend of refined asphalts and adhesion promoters is designed to bond rapidly to moist, damp, wet or dry surfaces. It provides water repellence, and is used on asphalt shingle roofs, asphalt composition roofs, concrete or masonry surfaces and sealing areas where dissimilar materials join: chimneys, gutters, valleys, etc. Trowel or putty knife apply at a rate of 12 ft ² , 1/8" thick per gallon.
Container Size:	5 gallons. Note all cautions on container label.
Systems Approvals:	Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance
Trade name:	# 450 Fiberated Emulsion Roof Coating, #400 Non-Fibrated Emulsion Roof Coating
Specifications:	ASTM D 1227 Type III Class I
Description:	A custom blend of refined asphalt, bitumen, water and thixotropic clay stabilizers. For use as protective coating on smooth asphalt and metal roofing systems, or for dampproofing masonry and concrete surfaces at an application rate of 1½-2gal/100 ft ² . per coating. Brush, roller, spray or squeegee applied.
Container Size:	5, 55 and 275 gallons. Note all cautions on container label.
Systems Approvals:	Methods of application and quantities shall comply with specific Roof Assembly, Product Control Notice of Acceptance

LIMITATIONS:

1. Fire classification is not part of this acceptance; refer to a current Approved Roofing Materials Directory for fire rating of this product.
2. All products shall be applied in strict compliance with Manufacturer's published application instructions.
3. American Industrial Manufacturer's products shall not be applied in inclement weather conditions.
4. The products listed herein are components of roof assemblies and are approved for use with roof assemblies that list any of the products listed herein as part of their roof assemblies Notice of Acceptance.
5. All products listed herein shall have a un-announced follow-up quality control program from an approved listing agency. Follow up test results shall be made available to Product Control Section upon request.
6. All approved products listed herein shall be labeled in compliance with TAS 121 and shall bear the imprint or identifiable marking of the manufacturer's name or logo and following statement: "Miami-Dade County Product Control Approved" or the Miami-Dade County Product Control Seal as shown below.



END OF THIS ACCEPTANCE



NOA No.: 12-0203.11
Expiration Date: 04/17/13
Approval Date: 05/24/12
Page 5 of 5